



ALIBI™

High Definition Surveillance



2.0 Megapixel

HD-TVI

2.0 MEGAPIXEL 1080P INDOOR MINI HD-TVI BOARD CAMERA WITH PINHOLE LENS

An ideal hidden camera solution when discretion is key

- + 2.0 MP Progressive Scan CMOS produces up to 1080p HD-quality video
- + 4.3 mm wide angle pinhole lens covers a large area
- + Digital Day/Night (ICR) and 2D-DNR features offer better low-light images
- + HD-TVI delivers zero latency HD video over RG59 coax or any standard analog CCTV cabling, minimizing upgrade efforts
- + Compact dimensions, measuring at 1.25" x 1.25", make it an ideal covert solution
- + Up the Coax (UTC) technology enables you to control the camera's onscreen display (OSD) from your web browser, digital video recorder interface such as the Alibi Central Management System or smart phone app
- + Operating temperature of 5° to 122°F

What's Included:

- + 2.0 MP Mini HD-TVI Board Camera with Pinhole Lens
- + Mounting hardware
- + Quick start guide



Advanced Energy Solutions
Clearwater, FL
TEL 888-518-0068
www.clearwatersecuritycameras.com



2.0 MEGAPIXEL 1080P INDOOR MINI HD-TVI BOARD CAMERA WITH PINHOLE LENS

SPECIFICATIONS

IMAGING SPECIFICATIONS

AGC Control	OSD Selectable
Camera Resolution	1080p
Day/Night Function	Digital
Digital Noise Reduction (DNR)	2D-DNR
Electronic Shutter (sec)	Auto, 1/25-1/1000
Effective Pixels (K)	1930 x 1088
Flip	Digital Horizontal/Vertical
Imager Size (in)	1/2.7
Imager Type	CMOS
IR Sensitive	No
Max Analog IPS (NTSC)	30
Megapixel	2MP
OSD	Yes - UTC

LENS SPECIFICATIONS

Focal Length (mm)	3.7
-------------------	-----

CONNECTORS

Video Out	HD-TVI BNC Only
-----------	-----------------

POWER REQUIREMENTS

Power Consumption (watts/mA)	100mA
Power Supply Included	No
Volts DC Input	12

PHYSICAL CHARACTERISTICS

Dimensions (in)	1.25" x 1.25"
Relative Humidity	Humidity less than 80%
Operating Temperature (F)	5°F-122°
Weight (oz)	1oz
Shipping Weight	.5

